

APPLICANT(S): HERSHKOVITS, Yehuda et al.
SERIAL NO.: 09/986,452
FILED: November 8, 2001
Page 2

AMENDMENTS TO CLAIMS

Please add or amend the claims to read as follows, and cancel without prejudice or disclaimer to resubmission in a divisional or continuation application claims indicated as cancelled:

1.-28.(Cancelled)

29. (Currently Amended) A method of transferring telecommunication transmissions comprising:

~~using~~ Using a PCI bus connector to establish a connection between a rear I/O card and a second front card or rear card, upon receiving a failure indication associated with a first front card ~~corresponding~~ connected via a through connection to said rear card.

C
30. (Currently Amended) A method of transferring telecommunication transmissions comprising:

connecting a rear I/O card to a set of backplane traces associated with a PCI bus of said backplane upon receiving a failure indication associated with a front card ~~corresponding~~ connected via a through connection to said rear card.

31. (Currently Amended) A method of transferring telecommunication transmissions comprising:

allocating at least a portion of a PCI bus for communications between a rear card and a backup front or rear card upon receiving a failure indication associated with a front card connected via a through connection to said rear card.

APPLICANT(S): HERSHKOVITS, Yehuda et al.
SERIAL NO.: 09/986,452
FILED: November 8, 2001
Page 3

32. (Currently Amended) A rear card of a device for transferring telecommunication transmissions, comprising:

an isolation relay adapted to route incoming signals from ~~a back~~ said rear card to a backup front or rear card through at least a portion of a PCI bus upon receiving a failure indication associated with a backup card currently connected via a through connection to said ~~back~~ rear card.

C
33. (Currently Amended) A device for transferring telecommunication transmissions, comprising:

a control circuit, which upon receiving a indication signal associated with a first front card currently connected via a through connection to a rear card, is adapted to redirect communications from said rear card to a second front card or a second rear card over at least a portion PCI bus.

34. (Previously Presented) A device according to claim 33, wherein said indication is received over at least a portion of said PCI bus.
